



# 工业电源

# 工业电源

## 推荐系列

### CHROME II 系列

5 V ~ 48 V, 15 W ~ 100 W

- Class II, 双重绝缘
- 符合 DIN 43880
- NEC Class 2 / Limited Power Source (LPS) 认证

### LYTE II 系列

12 V ~ 48 V, 75 W ~ 480 W

- 效率高达 93.5%
- 50°C 满功率输出
- 低空载功耗
- 内置恒流线路

### Force-GT 系列

12 V ~ 48 V, 120 W ~ 960 W

- 效率高达 95%
- 60°C (单相) 和 55°C (三相) 满功率输出
- 内置 DC OK 干接点
- 三防胶涂布



### PMT2 / PMT2 ECO 系列

12 V ~ 48 V 和双路输出, 35 W ~ 350 W

- 30 mm 低高度
- 低空载功耗
- 适合家用电器和工业设备

### PMR 系列

12 V ~ 48 V, 150 W ~ 1,500 W

- 低高度设计, 内置主动式 PFC
- 符合谐波电流 IEC/EN 61000-3-2, Class A 及 D 标准
- 适合家用电器和工业设备

### PMS 系列

24 V ~ 48 V, 750 W ~ 2,500 W


- 支持 PMBus®
- 并联均流
- 峰值功率, 适用于电机
- 最多支持 6 台并联

## 导轨型电源


### 经济型

系列	型号名称	PFC	输出			输入电压范围	尺寸 (毫米) (H × W × D)
			电压	电流	功率		
<b>CHROME II</b>  <ul style="list-style-type: none"> <li>• Class II, 双重绝缘</li> <li>• 符合 DIN 43880</li> <li>• 符合 DOE VI 效率</li> <li>• NEC Class 2 / Limited Power Source (LPS) 认证</li> <li>• 过压防护等级 III</li> </ul>	DRC-05V015W1RZ <span style="color: red;">新品</span>	5 V	5 V	2.4 A	12 W	85-264 V <sub>AC</sub>	87.5 × 18 × 55
	DRC-05V030W1RZ <span style="color: red;">新品</span>			3.0 A	15 W		87.5 × 35 × 55
	DRC-12V015W1RZ <span style="color: red;">新品</span>	12 V	12 V	1.25 A	15 W	85-264 V <sub>AC</sub>	87.5 × 18 × 55
	DRC-12V030W1RZ			2.0 A	24 W		87.5 × 35 × 55
	DRC-12V060W1RZ			4.5 A	54 W		87.5 × 52.5 × 55
	DRC-12V100W1RZ			7.1 A	85.2 W		87.5 × 70 × 55
	DRC-24V015W1RZ <span style="color: red;">新品</span>	24 V	24 V	0.63 A	15 W	85-264 V <sub>AC</sub>	87.5 × 18 × 55
	DRC-24V030W1RZ			1.5 A	36 W		87.5 × 35 × 55
	DRC-24V060W1RZ			2.5 A	60 W		87.5 × 52.5 × 55
	DRC-24V100W1RZ			3.83 A	91.92 W		87.5 × 70 × 55
	DRC-48V060W1RZ	48 V	48 V	1.25 A	60 W	85-264 V <sub>AC</sub>	87.5 × 52.5 × 55
	DRC-48V100W1RZ			1.92 A	92.16 W		87.5 × 70 × 55

### 经济型

系列	型号名称*	PFC	输出			输入电压范围	尺寸 (毫米) (H × W × D)
			电压	电流	功率		
<b>LYTE II (DIN ECO)</b>  <ul style="list-style-type: none"> <li>窄机身设计</li> <li>内置恒流线路</li> <li>50°C 满功率输出</li> <li>低空载功耗</li> </ul>	DRL-12V75W1AZ□		12 V	6.25 A	75 W	85-264 V <sub>AC</sub>	123.6 × 27 × 102
	DRL-24V75W1AZ□		24 V	3.125 A	75 W	85-264 V <sub>AC</sub>	123.6 × 27 × 102
	DRL-48V75W1AZ□		48 V	1.57 A	75.36 W	85-264 V <sub>AC</sub>	123.6 × 27 × 102
	DRL-12V120W1EN□		12 V	10.0 A	120 W	90-264 V <sub>AC</sub>	123.6 × 30 × 116.8
	DRL-12V240W1EN□	●		20.0 A	240 W		123.6 × 40 × 116.8
	DRL-24V120W1EN□		24 V	5.0 A	120 W	90-264 V <sub>AC</sub>	123.6 × 30 × 116.8
	DRL-24V240W1EN□	●		10.0 A	240 W		123.6 × 40 × 116.8
	DRL-24V480W1EN□	●		20.0 A	480 W		123.6 × 56 × 116.8
	DRL-48V120W1EN□		48 V	2.5 A	120 W	90-264 V <sub>AC</sub>	123.6 × 30 × 116.8
	DRL-48V240W1EN□	●		5.0 A	240 W		123.6 × 40 × 116.8
	DRL-48V480W1EN□	●		10.0 A	480 W		123.6 × 56 × 116.8
	DRL-24V120W3EN <small>即将推出</small>		24 V	5 A	120 W	3 × 340-575 V <sub>AC</sub>	123.6 × 40 × 116.8
	DRL-24V240W3EN <small>即将推出</small>			10 A	240 W		123.6 × 56 × 116.8
	DRL-24V480W3EN <small>即将推出</small>	●		20 A	480 W		123.6 × 60 × 142.6
	DRL-24V960W3EN <small>即将推出</small>	●		40 A	960 W		123.6 × 110 × 142.6
	DRL-48V120W3EN <small>即将推出</small>		48 V	2.5 A	120 W	3 × 340-575 V <sub>AC</sub>	123.6 × 40 × 116.8
	DRL-48V240W3EN <small>即将推出</small>			5 A	240 W		123.6 × 56 × 116.8
	DRL-48V480W3EN <small>即将推出</small>	●		10 A	480 W		123.6 × 60 × 142.6
	DRL-48V960W3EN <small>即将推出</small>	●		20 A	960 W		123.6 × 110 × 142.6

### 高性能

系列	型号名称*	PFC	输出			输入电压范围	尺寸 (毫米) (H × W × D)
			电压	电流	功率		
<b>Force-GT</b>  <ul style="list-style-type: none"> <li>窄机身设计, 效率高达 95%</li> <li>内置恒流线路</li> <li>三防胶涂布</li> <li>60°C (单相) 和 55°C (三相) 满功率输出</li> </ul>	DRF-12V120W1G□A	●	12 V	10.0 A	120 W	90-264 V <sub>AC</sub>	123.6 × 30 × 116.8
	DRF-12V240W1G□A	●		20.0 A	240 W	(直流输入范围 127-375 V <sub>DC</sub> )	123.6 × 40 × 116.8
	DRF-24V120W1G□A	●	24 V	5.0 A	120 W	90-264 V <sub>AC</sub> (直流输入范围 127-375 V <sub>DC</sub> )	123.6 × 30 × 116.8
	DRF-24V240W1G□A	●		10.0 A	240 W		123.6 × 40 × 116.8
	DRF-24V480W1G□A	●		20.0 A	480 W		123.6 × 56 × 116.8
	DRF-48V120W1G□A	●	48 V	2.5 A	120 W	90-264 V <sub>AC</sub> (直流输入范围 127-375 V <sub>DC</sub> )	123.6 × 30 × 116.8
	DRF-48V240W1G□A	●		5.0 A	240 W		123.6 × 40 × 116.8
	DRF-48V480W1G□A	●		10.0 A	480 W		123.6 × 56 × 116.8
	DRF-24V120W3G□A		24 V	5.0 A	120 W	3 × 320-575 V <sub>AC</sub> 或 2 × 340-575 V <sub>AC</sub> (直流输入范围 450-800 V <sub>DC</sub> )	124 × 38 × 125.3
	DRF-24V240W3G□A			10.0 A	240 W		124 × 50 × 125.3
	DRF-24V480W3G□A	●		20.0 A	480 W		124 × 65 × 127.3
	DRF-24V480W3G□A	●		40.0 A	960 W		124 × 110 × 128.7
	DRF-48V480W3G□A <small>新品</small>	●	48 V	10.0 A	480 W	3 × 320-575 V <sub>AC</sub> 或 2 × 340-575 V <sub>AC</sub> (直流输入范围 450-800 V <sub>DC</sub> )	124 × 65 × 127.3
	DRF-48V960W3G□A <small>新品</small>	●		20.0 A	960 W		124 × 110 × 128.7

### 特别设计



系列	型号名称	PFC	输出			输入电压范围	尺寸 (毫米) (H × W × D)
			电压	电流	功率		
<b>CliQ M</b>  <ul style="list-style-type: none"> <li>通过海事认证</li> <li>三防胶涂布</li> <li>增强型峰值功率 (APB)</li> </ul>	DRM-24V80W1PN	●	24 V	3.4 A	81.6 W	85-276 V <sub>AC</sub> (直流输入范围 88-375 V <sub>DC</sub> )	124 × 32 × 102
	DRM-24V120W1PN	●		5.0 A	120 W	85-264 V <sub>AC</sub> (直流输入范围 88-375 V <sub>DC</sub> )	124 × 40 × 117
	DRM-24V240W1PN	●		10.0 A	240 W	85-276 V <sub>AC</sub> (直流输入范围 88-375 V <sub>DC</sub> )	124 × 60 × 117
	DRM-24V480W1PN	●		20.0 A	480 W		124 × 82 × 127
	DRM-24V960W1PN	●		40.0 A	960 W	85-264 V <sub>AC</sub> (直流输入范围 110-375 V <sub>DC</sub> )	124 × 125 × 133.6
	DRM-24V480W3PN	●		20.0 A	480 W	3 × 320-600 V <sub>AC</sub> 或 2 × 380-600 V <sub>AC</sub> (直流输入范围 450-800 V <sub>DC</sub> )	124 × 65 × 127.1
	DRM-24V960W3PN	●		40.0 A	960 W		124 × 110 × 128.6
<b>CliQ VA</b>  <ul style="list-style-type: none"> <li>智能监控输出电流/电压和寿命预期</li> <li>三防胶涂布</li> <li>增强型峰值功率 (APB)</li> </ul>	DRV-24V120W1PN	●	24 V	5.0 A	120 W	85-264 V <sub>AC</sub> (直流输入范围 88-375 V <sub>DC</sub> )	124 × 60 × 139
	DRV-24V240W1PN	●		10.0 A	240 W	85-276 V <sub>AC</sub> (直流输入范围 88-375 V <sub>DC</sub> )	124 × 60 × 139
	DRV-24V480W1PN	●		20.0 A	480 W		124 × 82 × 149

\*对于可选项, 请参阅产品规格书

# 工业电源


## 平板型电源

### 经济型

系列	型号名称*	PFC	输出			输入电压范围	尺寸 (毫米) (L × W × H)
			电压	电流	功率		
<b>PMT2 ECO</b>  <ul style="list-style-type: none"> <li>• 额定高压输入 200-240 V<sub>AC</sub></li> <li>• 符合 EMC Class A</li> <li>• CCC/CQC 和 BIS 认证</li> </ul>	PMT-24V50W2BNJ <span>新品</span>	24 V	2.2 A	52.8 W	180-264 V <sub>AC</sub>	99 × 82 × 29	
	PMT-24V75W2BNJ <span>新品</span>		3.2 A	76.8 W		99 × 97 × 30	
	PMT-24V100W2BNJ <span>新品</span>		4.5 A	108 W		129 × 97 × 30	
	PMT-24V150W2BNJ <span>新品</span>		6.25 A	150 W		159 × 97 × 30	
	PMT-24V200W2BNJ <span>新品</span>		8.8 A	211.2 W		159 × 97 × 30	
	PMT-24V350W2BNJ <span>新品</span>		14.6 A	350.4 W		215 × 115 × 30	
	PMT-48V50W2BNJ <span>新品</span>	48 V	1.1 A	52.8 W	180-264 V <sub>AC</sub>	99 × 82 × 29	
	PMT-48V75W2BNJ <span>新品</span>		1.6 A	76.8 W		99 × 97 × 30	
	PMT-48V100W2BNJ <span>新品</span>		2.3 A	110 W		129 × 97 × 30	
	PMT-48V150W2BNJ <span>新品</span>		3.3 A	158.4 W		159 × 97 × 30	
	PMT-48V200W2BNJ <span>新品</span>		4.4 A	211.2 W		159 × 97 × 30	
	PMT-48V350W2BNJ <span>新品</span>		7.3 A	350.4 W		215 × 115 × 30	
	<b>PMT2</b>  <ul style="list-style-type: none"> <li>• 30 mm 低高度</li> <li>• 符合 IEC 60335, IEC 61558</li> </ul>	PMT-12V35W2BA□	12 V	3.0 A	36 W	90-264 V <sub>AC</sub>	99 × 82 × 29
		PMT-12V50W2BA□		4.2 A	50.4 W		99 × 82 × 29
PMT-12V75W2BA□		6.0 A		72 W	99 × 97 × 30		
PMT-12V100W2BA□		8.5 A		102 W	129 × 97 × 30		
PMT-12V150W2BA□		12.5 A		150 W	90-132 V <sub>AC</sub> , 180-264 V <sub>AC</sub> (选择开关)	159 × 97 × 30	
PMT-12V150W2CA□		12.5 A		150 W	90-264 V <sub>AC</sub>	159 × 97 × 30	
PMT-12V200W2BM□		17.0 A		204 W		159 × 97 × 30	
PMT-12V200W2BR□		17.0 A		204 W	90-132 V <sub>AC</sub> , 180-264 V <sub>AC</sub> (选择开关)	159 × 97 × 30	
PMT-12V350W2BM□		29.0 A		348 W		215 × 115 × 30	
PMT-12V350W2BR□		29.0 A		348 W		215 × 115 × 30	
PMT-15V35W2BA		15 V		2.4 A	36 W	90-264 V <sub>AC</sub>	99 × 82 × 29
PMT-15V50W2BA				3.4 A	51 W		99 × 82 × 29
PMT-15V75W2BA			5.0 A	75 W	99 × 97 × 30		
PMT-15V100W2BA			7.0 A	105 W	129 × 97 × 30		
PMT-15V150W2BA			10.0 A	150 W	90-132 V <sub>AC</sub> , 180-264 V <sub>AC</sub> (选择开关)	159 × 97 × 30	
PMT-15V150W2CA			10.0 A	150 W	90-264 V <sub>AC</sub>	159 × 97 × 30	
PMT-24V35W2BA□		24 V	1.5 A	36 W	90-264 V <sub>AC</sub>	99 × 82 × 29	
PMT-24V50W2BA□			2.2 A	52.8 W		99 × 82 × 29	
PMT-24V75W2BA□			3.2 A	76.8 W		99 × 97 × 30	
PMT-24V100W2BA□			4.5 A	108 W		129 × 97 × 30	
PMT-24V150W2BA□			6.25 A	150 W	90-132 V <sub>AC</sub> , 180-264 V <sub>AC</sub> (选择开关)	159 × 97 × 30	
PMT-24V150W2CA□			6.25 A	150 W	90-264 V <sub>AC</sub>	159 × 97 × 30	
PMT-24V200W2BM□			8.8 A	211.2 W		159 × 97 × 30	
PMT-24V200W2BR□			8.8 A	211.2 W	90-132 V <sub>AC</sub> , 180-264 V <sub>AC</sub> (选择开关)	159 × 97 × 30	
PMT-24V350W2BM□			14.6 A	350.4 W		215 × 115 × 30	
PMT-24V350W2BR□			14.6 A	350.4 W		215 × 115 × 30	
PMT-30V35W2BA			30 V	1.2 A	36 W	90-264 V <sub>AC</sub>	99 × 82 × 29
PMT-30V50W2BA				1.7 A	51 W		99 × 82 × 29
PMT-30V75W2BA		2.5 A		75 W	99 × 97 × 30		
PMT-30V100W2BA		3.6 A		108 W	129 × 97 × 30		
PMT-30V150W2BA		5.0 A		150 W	90-132 V <sub>AC</sub> , 180-264 V <sub>AC</sub> (选择开关)	159 × 97 × 30	
PMT-30V150W2CA		5.0 A		150 W	90-264 V <sub>AC</sub>	159 × 97 × 30	
PMT-36V35W2BA		36 V	1.0 A	36 W	90-264 V <sub>AC</sub>	99 × 82 × 29	
PMT-36V50W2BA			1.45 A	52.2 W		99 × 82 × 29	
PMT-36V75W2BA			2.1 A	75.6 W		99 × 97 × 30	
PMT-36V100W2BA			3.0 A	108 W	129 × 97 × 30		
PMT-36V150W2BA	4.3 A		154.8 W	90-132 V <sub>AC</sub> , 180-264 V <sub>AC</sub> (选择开关)	159 × 97 × 30		
PMT-36V150W2CA	4.3 A		154.8 W	90-264 V <sub>AC</sub>	159 × 97 × 30		

\*对于可选项, 请参阅产品规格书

### 经济型

系列	型号名称*	PFC	输出			输入电压范围	尺寸 (毫米) (L × W × H)
			电压	电流	功率		
<b>PMT2</b>  • 30 mm 低高度 • 符合 IEC 60335, IEC 61558	PMT-36V200W2BM		36 V	5.9 A	212.4 W	90-132V <sub>AC</sub> , 180-264V <sub>AC</sub> (选择开关)	159 × 97 × 30
	PMT-36V200W2BR			5.9 A	212.4 W		159 × 97 × 30
	PMT-36V350W2BM			9.7 A	349.2 W		215 × 115 × 30
	PMT-36V350W2BR			9.7 A	349.2 W		215 × 115 × 30
	PMT-48V35W2BA		48 V	0.8 A	38.4 W	90-264 V <sub>AC</sub>	99 × 82 × 29
	PMT-48V50W2BA			1.1 A	52.8 W		99 × 82 × 29
	PMT-48V75W2BA			1.6 A	76.8 W		99 × 97 × 30
	PMT-48V100W2BA			2.3 A	110.4 W	129 × 97 × 30	
	PMT-48V150W2BA			3.3 A	158.4 W	90-132V <sub>AC</sub> , 180-264V <sub>AC</sub> (选择开关)	159 × 97 × 30
	PMT-48V150W2CA			3.3 A	158.4 W	90-264 V <sub>AC</sub>	159 × 97 × 30
	PMT-48V200W2BM			4.4 A	211.2 W	90-132V <sub>AC</sub> , 180-264V <sub>AC</sub> (选择开关)	159 × 97 × 30
	PMT-48V200W2BR			4.4 A	211.2 W		159 × 97 × 30
	PMT-48V350W2BM			7.3 A	350.4 W		215 × 115 × 30
	PMT-48V350W2BR			7.3 A	350.4 W		215 × 115 × 30
	PMT-D1V75W2□A		5 V/12 V	5.0 A/4.0 A	73 W	90-264 V <sub>AC</sub>	129 × 97 × 30
	PMT-D2V75W2□A		5 V/24 V	5.0 A/2.1 A	75.4 W	90-264 V <sub>AC</sub>	129 × 97 × 30

### 高性能

系列	型号名称	PFC	输出			输入电压范围	尺寸 (毫米) (L × W × H)
			电压	电流	功率		
<b>PMR</b>  • 内置 PFC • 符合 IEC 60335, IEC 61558 • 30 mm 低高度	PMR-12V150W1AT	●	12 V	12.5 A	150 W	90-264 V <sub>AC</sub> (直流输入范围 127-375 V <sub>DC</sub> )	129 × 97 × 30
	PMR-12V240W1AT	●		20.0 A	240 W		159 × 97 × 30
	PMR-12V320W1AT	●		26.7 A	320.4 W		215 × 115 × 30
	PMR-12V600W1BT	●		50.0 A	600 W		225 × 124 × 41
	PMR-12V1K0W1BT <small>即将推出</small>	●		60.0 A	720 W		225 × 124 × 41
	PMR-24V150W1AT	●	24 V	6.5 A	156 W	90-264 V <sub>AC</sub> (直流输入范围 127-375 V <sub>DC</sub> )	129 × 97 × 30
	PMR-24V240W1AT	●		10.0 A	240 W		159 × 97 × 30
	PMR-24V320W1AT	●		13.4 A	321.6 W		215 × 115 × 30
	PMR-24V600W1BT	●		25.0 A	600 W		225 × 124 × 41
	PMR-24V1K0W1BT <small>即将推出</small>	●		42.0 A	1,008 W		225 × 124 × 41
	PMR-24V1K5W1BTB <small>新品</small>	●	62.5 A	1,500 W	90-264 V <sub>AC</sub>	204 × 127 × 40.5	
	PMR-36V150W1AT	●	36 V	4.3 A	154.8 W	90-264 V <sub>AC</sub> (直流输入范围 127-375 V <sub>DC</sub> )	129 × 97 × 30
	PMR-36V240W1AT	●		6.7 A	241.2 W		159 × 97 × 30
	PMR-36V320W1AT	●		8.9 A	320.4 W		215 × 115 × 30
	PMR-36V600W1BT	●		16.6 A	597.6 W		225 × 124 × 41
	PMR-36V1K0W1BT <small>即将推出</small>	●		28.0 A	1,008 W		225 × 124 × 41
	PMR-48V150W1AT	●	48 V	3.3 A	158.4 W	90-264 V <sub>AC</sub> (直流输入范围 127-375 V <sub>DC</sub> )	129 × 97 × 30
	PMR-48V240W1AT	●		5.0 A	240 W		159 × 97 × 30
	PMR-48V320W1AT	●		6.7 A	321.6 W		215 × 115 × 30
	PMR-48V600W1BT	●		12.5 A	600 W		225 × 124 × 41
PMR-48V1K0W1BT <small>即将推出</small>	●	21.0 A		1,008 W	225 × 124 × 41		
PMR-48V1K5W1BTC <small>新品</small>	●	31.25 A	1,500 W	90-264 V <sub>AC</sub>	204 × 127 × 40.5		

### 特别设计

系列	型号名称	PFC	输出			输入电压范围	尺寸 (毫米) (L × W × H)
			电压	电流	功率		
<b>PMS</b>  • 支持 PMBus® • 峰值功率, 适用于电机 • 最多支持 6 台并联以提高输出功率	PMS-24V750W1BTD <small>新品</small>	●	24 V	31.25 A	750 W	85-264 V <sub>AC</sub>	177.8 × 101.6 × 40
	PMS-24V1K2W1BTD <small>新品</small>	●		50.0 A	1,200 W		204 × 127 × 40.5
	PMS-24V2K5W1BMD <small>新品</small>	●		104.2 A	2,500 W		271 × 127 × 40.5
	PMS-48V750W1BTD <small>新品</small>	●	48 V	15.63 A	750 W	85-264 V <sub>AC</sub>	177.8 × 101.6 × 40
	PMS-48V1K2W1BTD <small>新品</small>	●		25.0 A	1,200 W		204 × 127 × 40.5
	PMS-48V2K5W1BMD <small>新品</small>	●		52.1 A	2,500 W		271 × 127 × 40.5

\*对于可选项, 请参阅产品规格书

## 开架型电源

### 经济型

系列	型号名称*	PFC	输出					输入电压范围	尺寸 (毫米) (L × W × H)	
			电压	自然对流		强制风冷			开架型	
				电流	功率	电流	功率			
 <ul style="list-style-type: none"> <li>小尺寸</li> <li>多种端子可选</li> </ul>	PJT-12V40WBA□		12 V	3.33 A	40 W	-	-	90-264 V <sub>AC</sub>	76.2 × 50.8 × 22.9	
	PJT-12V65WBA□			5.0 A	60 W	-	-		101.6 × 50.8 × 30	
	PJT-12V100WBA□	●		8.33 A	100 W	-	-		127 × 76.2 × 31	
	PJT-12V100WBB□			6.67 A	80 W	8.33 A	100 W		101.6 × 50.8 × 31.8	
	PJT-15V40WBA□		15 V	2.67 A	40 W	-	-	90-264 V <sub>AC</sub>	76.2 × 50.8 × 22.9	
	PJT-15V65WBA□			4.2 A	63 W	-	-		101.6 × 50.8 × 30	
	PJT-15V100WBA□	●		6.67 A	100 W	-	-		127 × 76.2 × 31	
	PJT-15V100WBB□			5.33 A	80 W	6.67 A	100 W		101.6 × 50.8 × 31.8	
	PJT-18V40WBA□		18 V	2.22 A	40 W	-	-	90-264 V <sub>AC</sub>	76.2 × 50.8 × 22.9	
	PJT-18V65WBA□			3.61 A	65 W	-	-		101.6 × 50.8 × 30	
	PJT-18V100WBA□	●		5.55 A	100 W	-	-		127 × 76.2 × 31	
	PJT-18V100WBB□			4.44 A	80 W	5.55 A	100 W		101.6 × 50.8 × 31.8	
	PJT-24V40WBA□		24 V	1.66 A	40 W	-	-	90-264 V <sub>AC</sub>	76.2 × 50.8 × 22.9	
	PJT-24V65WBA□			2.71 A	65 W	-	-		101.6 × 50.8 × 30	
	PJT-24V100WBA□	●		4.17 A	100 W	-	-		127 × 76.2 × 31	
	PJT-24V100WBB□			3.33 A	80 W	4.17 A	100 W		101.6 × 50.8 × 31.8	

### 高性能

系列	型号名称*	PFC	输出					输入电压范围	尺寸 (毫米) (L × W × H)	
			电压	自然对流		强制风冷			开架型	内置机壳型
				电流	功率	电流	功率			
 <ul style="list-style-type: none"> <li>多种可选配置</li> <li>三防胶涂布</li> </ul>	PJ-5V15W□NA		5 V	3.0 A	15 W	-	-	85-264 V <sub>AC</sub>	87.5 × 50 × 22	107.5 × 60 × 32
	PJ-12V15W□NA		12 V	1.3 A	15.6 W	-	-	85-264 V <sub>AC</sub>	87.5 × 50 × 22	107.5 × 60 × 32
	PJ-12V30W□NA			2.5 A	30 W	-	-		105 × 50 × 25.6	125 × 60 × 36
	PJ-12V50W□NA	●		4.3 A	51.6 W	-	-		132 × 50 × 26.6	162 × 60 × 36
	PJ-12V100W□□A	●		8.5 A	102 W	-	-		155 × 62 × 33.5	185 × 72 × 45
	PJ-12V150W□□A	●		12.5 A	150 W	-	-		160 × 75 × 37	188 × 85 × 47
	PJ-24V30W□NA		24 V	1.25 A	31.2 W	-	-	85-264 V <sub>AC</sub>	105 × 50 × 25.6	125 × 60 × 36
	PJ-24V50W□NA	●		2.1 A	50.4 W	-	-		132 × 50 × 26.6	162 × 60 × 36
	PJ-24V100W□□A	●		4.3 A	103.2 W	-	-		155 × 62 × 33.5	185 × 72 × 45
	PJ-24V150W□□A	●		6.3 A	150 W	-	-		160 × 75 × 37	188 × 85 × 47
PJ-48V50W□NA	●	48 V	1.1 A	52.8 W	-	-	85-264 V <sub>AC</sub>	132 × 50 × 26.6	162 × 60 × 36	
 <ul style="list-style-type: none"> <li>内置 PFC</li> <li>功率增强长达 10s</li> <li>三防胶涂布</li> </ul>	PJB-24V100W□□A	●	24 V	4.3 A	103.2 W	-	-	85-264 V <sub>AC</sub>	155 × 62 × 33.5	185 × 72 × 45
	PJB-24V150W□□A	●		6.3 A	151.2 W	-	-		160 × 75 × 37	188 × 85 × 47
	PJB-24V240W□□A	●		10.0 A	240 W	-	-		180 × 84 × 42	212 × 98 × 59
	PJB-24V300W□□A	●		12.5 A	300 W	-	-		222 × 95 × 53.6	252 × 108 × 66

\*对于可选项, 请参阅产品规格书


## 导轨型功能模块

产品类型	系列	型号名称*	输出		输入电流	输入电压范围	尺寸 (毫米) (H × W × D)
			电压	电流			
<b>冗余模块</b> 	CliQ II	DRR-20A	22-60 V	20.0 A	(1+1 冗余) = 标称 2 × 12.5 A (N+1 冗余) = 标称 2 × 10 A	22-60 V <sub>DC</sub>	121 × 50 × 122.1
		DRR-20N					121 × 50 × 122.1
		DRR-40A	22-60 V	40.0 A	(1+1 冗余) = 标称 2 × 25 A (N+1 冗余) = 标称 2 × 20 A	22-60 V <sub>DC</sub>	121 × 50 × 122.1
		DRR-40N					121 × 50 × 122.1
<b>缓冲模块</b> 	CliQ II	DRB-24V020AB□	24 V	20.0 A	充电模式: < 0.6 A	22.8-28.8 V <sub>DC</sub>	121 × 70 × 120.1
		DRB-24V040ABN					40.0 A
<b>直流不间断电源模块</b> 	CliQ II	DRU-24V40ABN	24 V	40.0 A	充电模式: 2.0 A ± 1.0 A	24-28 V <sub>DC</sub>	121 × 50 × 117.3
	CHROME	DRU-24V10ACZ	24 V	10.0 A	充电模式: 0.5 A ± 0.1 A	24-28 V <sub>DC</sub>	91 × 71 × 55.6
	CliQ M	DRU-24V10AMN	24 V	10.0 A	0.5 A, 1 A, 1.5 A, 2 A (typ.) (恒流)	18-30 V <sub>DC</sub>	124 × 38 × 117
		DRU-24V20AMN		20.0 A	0.75 A, 1.5 A, 2.25 A, 3 A (typ.) (恒流)	18-30 V <sub>DC</sub>	124 × 38 × 117
		DRU-24V40AMN		40.0 A	1 A, 2 A, 3 A, 4 A (typ.) (恒流)	18-30 V <sub>DC</sub>	124 × 50 × 117

\*对于可选项, 请参阅产品规格书

产品类型	系列	型号名称	额定电压	充电电流	放电电流	尺寸 (毫米) (H × W × D)
<b>电池舱模块 (不配电池)</b> 	CliQ M	DRN-24V7AAEN	24 V	2.1 A Max	40.0 A Max	211.5 × 148 × 109.2

## 适配器

系列	型号名称	CC 代码	输出			输入电压范围	尺寸 (毫米) (L × W × H)
			电压	电流	功率		
<b>ADT</b>  <ul style="list-style-type: none"> <li>紧凑型</li> <li>DoE Level VI 和 CoC Tier 2</li> </ul>	ADT-060A12AA	B-A	12 V	5.0 A	60 W	85-264 V <sub>AC</sub>	108 × 46 × 29.5
	ADT-060A12AB	B-A		5.0 A	60 W		108 × 46 × 29.5
	ADT-150B12AA	J-A		12.5 A	150 W	90-264 V <sub>AC</sub>	155 × 76 × 30
	ADT-060A15AA	B-A	15 V	4.0 A	60 W	85-264 V <sub>AC</sub>	108 × 46 × 29.5
	ADT-060A15AB	B-A		4.0 A	60 W		108 × 46 × 29.5
	ADT-060A19AA	B-A	19 V	3.2 A	60.8 W	85-264 V <sub>AC</sub>	108 × 46 × 29.5
	ADT-060A19AB	B-A		3.2 A	60.8 W		108 × 46 × 29.5
	ADT-120A19AA	M-A		6.15 A	120 W	90-264 V <sub>AC</sub>	138 × 68.5 × 24.5
	ADT-150A19AA	G-A	7.7 A	150 W	90-264 V <sub>AC</sub>	160 × 76.2 × 25.8	
	ADT-060A24AA	B-A	24 V	2.5 A	60 W	85-264 V <sub>AC</sub>	108 × 46 × 29.5
	ADT-060A24AB	B-A		2.5 A	60 W		108 × 46 × 29.5
	ADT-090A24AA	F-A		3.75 A	90 W	90-264 V <sub>AC</sub>	126 × 51 × 30
	ADT-120A24AA	F-A		5.0 A	120 W		138 × 68.5 × 24.5
	ADT-150A24AA	H-A		6.25 A	150 W		160 × 76.2 × 25.8
ADT-150C24AC	K-A	6.25 A		150 W	165.1 × 76.1 × 31.5		

# 全球运营与服务据点

## 亚洲

### Delta Electronics, Inc.

3 Tungyuan Road, Chungli Industrial Zone,  
Taoyuan County 32063, Taiwan, R.O.C.

TEL: +886 3 452 6107

FAX: +886 3 452 7314

### Delta Electronics (Shanghai) Co., Ltd China Headquarters

No. 182 Minyu Road, Pudong,  
Shanghai, P.R.C. 201209

TEL: +86 21 6872 3988

FAX: +86 21 6872 3996

### Delta Electronics (Thailand) PCL.

909 Soi 9, Moo 4, Bangpoo Industrial Estate  
(E.P.Z.), Pattana 1 Rd., T. Phrakasa, A. Muang,  
Samutprakarn 10280, Thailand

TEL: +66 2 709 2800

FAX: +66 2 709 2827

### Delta Electronics India Pvt. Ltd.

Plot No. 43, Sector - 35, HSIIDC,  
Gurgaon, Haryana 122001

TEL: +91 124 4874 900

+91 124 4169 040

FAX: +91 124 4874 945

### Delta Electronics (Japan), Inc.

2-1-14 Minato-ku Shibadaimon,  
Tokyo, 105-0012, Japan

TEL: +81 3 5733 1111

FAX: +81 3 5733 1211

### Delta Electronics (Korea), Inc.

1504, Byucksan Digital Valley 6-Cha,  
Gasan-dong, Geumcheon-gu, Seoul,  
153-704, Korea

TEL: +82 2 515 5303

+82 2 515 5305

FAX: +82 2 515 5302

### Delta Electronics (Australia) Pty Ltd

20-21, 45 Normanby Rd.  
Nothing Hill, VIC 3168, Australia

TEL: +61 9543 3720

FAX: +61 9544 0606

### Delta Energy Systems (Singapore) Pte Ltd

4 Kaki Bukit Avenue 1  
#05-04, Singapore 417939

TEL: +65 6747 5155

FAX: +65 6744 9228

## 北美

### Delta Electronics (Americas) Ltd. North American Headquarters

46101 Fremont Blvd.

Fremont, CA 94538, U.S.A.

TEL: +1 510 668 5100

FAX: +1 510 668 0680

## 中美洲和南美洲

### Delta Electronics International Mexico S.A. de C.V.

Centrum Park, Av. Gustavo Baz Prada 309  
Edificio E Planta Baja, Col. La Loma, C.P.

54030 Tlalnepantla, Estado de México

TEL: +52 55 3603 9200

### Delta Electronics (Brasil) Ltda

Estrada Velha Rio São Paulo, 5300-  
Eugênio de Melo, 12247-001-São José dos  
Campos-SP- Brasil

TEL: +55 12 3932 2300

## 欧洲

### Delta Electronics (Netherlands) B.V. EMEA Headquarters

Zandsteen 15

2132 MZ Hoofddorp, The Netherlands

TEL: +31 20 800 3900

Automotive Campus 260

5708 JZ Helmond, The Netherlands

TEL: +31 40 800 3900

### Delta Greentech Elektronik (Turkey)

Şerifali Mah. Hendem Cad. Kule Sok. No: 16-A,  
Ümraniye, İstanbul, Turkey

TEL: +90 216 499 99 10

FAX: +90 216 499 80 70

官网

微信



🌐 [www.DeltaPSU.cn](http://www.DeltaPSU.cn)

✉ [sps.reply.chn@deltaww.com](mailto:sps.reply.chn@deltaww.com)