



# Industrial Power Supplies

# Industrial Power Supplies

## Featured Series

### CHROME II Series

5 V ~ 48 V, 15 W ~ 100 W

- Class II, double isolation
- Compliant with DIN 43880
- NEC Class 2 / Limited Power Source (LPS) certified

### LYTE II Series

12 V ~ 48 V, 75 W ~ 480 W

- High efficiency up to 93.5%
- Full power up to 50°C
- Low no-load power consumption
- Built-in constant current circuit

### Force-GT Series

12 V ~ 48 V, 120 W ~ 960 W

- High efficiency up to 95%
- Full power up to 60°C (1-Phase)
- Built-in DC OK relay contact
- Conformal coating on PCBAs



### PMT2 / PMT2 ECO Series

12 V ~ 48 V and Dual, 35 W ~ 350 W

- Low profile < 1U design
- Low no-load power consumption
- Suitable for household and industrial applications

### PMR Series

12 V ~ 48 V, 150 W ~ 1,500 W

- Low profile with built-in active PFC
- Harmonic current IEC/EN 61000-3-2, Class A & D
- Suitable for household and industrial applications


### PMS Series

24 V ~ 48 V, 750 W ~ 2,500 W


- Support PMBus®
- Current sharing
- Peak power for motor drives
- Supports parallel connection of up to 6 power supplies

## DIN Rail Power Supplies


### ECONOMIC

Series	Model Name	PFC	Output			Input Voltage Range	Dimensions (mm) (H x W x D)
			Voltage	Current	Power		
<b>CHROME II</b>  <ul style="list-style-type: none"> <li>• Class II, double isolation</li> <li>• Compliant with DIN 43880</li> <li>• Meet DOE Level VI</li> <li>• NEC Class 2 / Limited Power Source (LPS) certified</li> <li>• Over Voltage Category III</li> </ul>	DRC-05V015W1RZ		5 V	2.4 A	12 W	85-264 V <sub>AC</sub>	87.5 x 18 x 55
	DRC-05V030W1RZ			3.0 A	15 W		87.5 x 35 x 55
	DRC-12V015W1RZ		12 V	1.25 A	15 W	85-264 V <sub>AC</sub>	87.5 x 18 x 55
	DRC-12V030W1RZ			2.0 A	24 W		87.5 x 35 x 55
	DRC-12V060W1RZ			4.5 A	54 W		87.5 x 52.5 x 55
	DRC-12V100W1RZ			7.1 A	85.2 W		87.5 x 70 x 55
	DRC-24V015W1RZ		24 V	0.63 A	15 W	85-264 V <sub>AC</sub>	87.5 x 18 x 55
	DRC-24V030W1RZ			1.5 A	36 W		87.5 x 35 x 55
	DRC-24V060W1RZ			2.5 A	60 W		87.5 x 52.5 x 55
	DRC-24V100W1RZ			3.83 A	91.92 W		87.5 x 70 x 55
	DRC-48V060W1RZ		48 V	1.25 A	60 W	85-264 V <sub>AC</sub>	87.5 x 52.5 x 55
	DRC-48V100W1RZ			1.92 A	92.16 W		87.5 x 70 x 55



## ECONOMIC

Series	Model Name <sup>1)</sup>	PFC	Output			Input Voltage Range	Dimensions (mm) (H x W x D)		
			Voltage	Current	Power				
<b>LYTE II (DIN ECO)</b>  <ul style="list-style-type: none"> <li>Slim design</li> <li>Built-in constant current circuit</li> <li>Full power up to 50°C</li> <li>Low no-load power consumption</li> </ul>	DRL-12V75W1AZ□		12 V	6.25 A	75 W	85-264 V <sub>AC</sub>	123.6 × 27 × 102		
	DRL-24V75W1AZ□		24 V	3.125 A	75 W	85-264 V <sub>AC</sub>	123.6 × 27 × 102		
	DRL-48V75W1AZ□		48 V	1.57 A	75.36 W	85-264 V <sub>AC</sub>	123.6 × 27 × 102		
	DRL-12V120W1EN□		12 V	10.0 A	120 W	90-264 V <sub>AC</sub>	123.6 × 30 × 116.8		
	DRL-12V240W1EN□	●		20.0 A	240 W		123.6 × 40 × 116.8		
	DRL-24V120W1EN□		24 V	5.0 A	120 W	90-264 V <sub>AC</sub>	123.6 × 30 × 116.8		
	DRL-24V240W1EN□	●		10.0 A	240 W		123.6 × 40 × 116.8		
	DRL-24V480W1EN□	●		20.0 A	480 W		123.6 × 56 × 116.8		
	DRL-48V120W1EN□		48 V	2.5 A	120 W	90-264 V <sub>AC</sub>	123.6 × 30 × 116.8		
	DRL-48V240W1EN□	●		5.0 A	240 W		123.6 × 40 × 116.8		
	DRL-48V480W1EN□	●		10.0 A	480 W		123.6 × 56 × 116.8		
	DRL-24V120W3EN <sup>2)</sup>			24 V	5 A		120 W	3 x 340-575 V <sub>AC</sub>	123.6 × 40 × 116.8
	DRL-24V240W3EN <sup>2)</sup>		10 A		240 W	123.6 × 56 × 116.8			
	DRL-24V480W3EN <sup>2)</sup>	●	20 A		480 W	123.6 × 60 × 142.6			
	DRL-24V960W3EN <sup>2)</sup>	●	40 A		960 W	123.6 × 110 × 142.6			
	DRL-48V120W3EN <sup>2)</sup>		48 V		2.5 A	120 W	3 x 340-575 V <sub>AC</sub>		123.6 × 40 × 116.8
	DRL-48V240W3EN <sup>2)</sup>				5 A	240 W			123.6 × 56 × 116.8
	DRL-48V480W3EN <sup>2)</sup>	●		10 A	480 W	123.6 × 60 × 142.6			
DRL-48V960W3EN <sup>2)</sup>	●	20 A		960 W	123.6 × 110 × 142.6				

## HIGH PERFORMANCE

Series	Model Name <sup>1)</sup>	PFC	Output			Input Voltage Range	Dimensions (mm) (H x W x D)
			Voltage	Current	Power		
<b>Force-GT</b>  <ul style="list-style-type: none"> <li>Slim design with high efficiency up to 95%</li> <li>Built-in constant current circuit</li> <li>Conformal coating</li> <li>Full power up to 60°C (1-Phase) &amp; 55°C (3-Phase)</li> </ul>	DRF-12V120W1G□A	●	12 V	10.0 A	120 W	90-264 V <sub>AC</sub> (DC input range 127-375 V <sub>DC</sub> )	123.6 × 30 × 116.8
	DRF-12V240W1G□A	●		20.0 A	240 W		123.6 × 40 × 116.8
	DRF-24V120W1G□A	●	24 V	5.0 A	120 W	90-264 V <sub>AC</sub> (DC input range 127-375 V <sub>DC</sub> )	123.6 × 30 × 116.8
	DRF-24V240W1G□A	●		10.0 A	240 W		123.6 × 40 × 116.8
	DRF-24V480W1G□A	●		20.0 A	480 W		123.6 × 56 × 116.8
	DRF-48V120W1G□A	●	48 V	2.5 A	120 W	90-264 V <sub>AC</sub> (DC input range 127-375 V <sub>DC</sub> )	123.6 × 30 × 116.8
	DRF-48V240W1G□A	●		5.0 A	240 W		123.6 × 40 × 116.8
	DRF-48V480W1G□A	●		10.0 A	480 W		123.6 × 56 × 116.8
	DRF-24V120W3G□A		24 V	5.0 A	120 W	3 x 320-575 V <sub>AC</sub> or 2 x 340-575 V <sub>AC</sub> (DC input range 450-800 V <sub>DC</sub> )	124 × 38 × 125.3
	DRF-24V240W3G□A			10.0 A	240 W		124 × 50 × 125.3
	DRF-24V480W3G□A	●		20.0 A	480 W		124 × 65 × 127.3
	DRF-24V960W3G□A	●		40.0 A	960 W		124 × 110 × 128.7
	DRF-48V480W3G□A	●	48 V	10.0 A	480 W	3 x 320-575 V <sub>AC</sub> or 2 x 340-575 V <sub>AC</sub> (DC input range 450-800 V <sub>DC</sub> )	124 × 65 × 127.3
DRF-48V960W3G□A	●	20.0 A		960 W	124 × 110 × 128.7		

## SPECIAL DESIGNS

Series	Model Name	PFC	Output			Input Voltage Range	Dimensions (mm) (H x W x D)
			Voltage	Current	Power		
<b>CliQ M</b>  <ul style="list-style-type: none"> <li>Maritime approvals</li> <li>Conformal coating</li> <li>Advanced Power Boost</li> </ul>	DRM-24V80W1PN	●	24 V	3.4 A	81.6 W	85-276 V <sub>AC</sub> (DC input range 88-375 V <sub>DC</sub> )	124 × 32 × 102
	DRM-24V120W1PN	●		5.0 A	120 W	85-264 V <sub>AC</sub> (DC input range 88-375 V <sub>DC</sub> )	124 × 40 × 117
	DRM-24V240W1PN	●		10.0 A	240 W	85-276 V <sub>AC</sub> (DC input range 88-375 V <sub>DC</sub> )	124 × 60 × 117
	DRM-24V480W1PN	●		20.0 A	480 W		124 × 82 × 127
	DRM-24V960W1PN	●		40.0 A	960 W	85-264 V <sub>AC</sub> (DC input range 110-375 V <sub>DC</sub> )	124 × 125 × 133.6
	DRM-24V480W3PN	●		20.0 A	480 W	3 x 320-600 V <sub>AC</sub> or 2 x 380-600 V <sub>AC</sub> (DC input range 450-800 V <sub>DC</sub> )	124 × 65 × 127.1
	DRM-24V960W3PN	●		40.0 A	960 W		124 × 110 × 128.6
<b>CliQ VA</b>  <ul style="list-style-type: none"> <li>Smart monitoring for output and lifetime expectancy</li> <li>Conformal coating</li> <li>Advanced Power Boost</li> </ul>	DRV-24V120W1PN	●	24 V	5.0 A	120 W	85-264 V <sub>AC</sub> (DC input range 88-375 V <sub>DC</sub> )	124 × 60 × 139
	DRV-24V240W1PN	●		10.0 A	240 W	85-276 V <sub>AC</sub> (DC input range 88-375 V <sub>DC</sub> )	124 × 60 × 139
	DRV-24V480W1PN	●		20.0 A	480 W		124 × 82 × 149



1) For options, please refer to the technical datasheet  
 2) Coming soon



# Industrial Power Supplies


## Panel Mount Power Supplies

### ECONOMIC


Series	Model Name <sup>1)</sup>	PFC	Output			Input Voltage Range	Dimensions (mm) (L x W x H)	
			Voltage	Current	Power			
<b>PMT2 ECO</b>  <ul style="list-style-type: none"> <li>High line nominal input voltage 200-240 V<sub>AC</sub></li> <li>Compliance to EMC Class A</li> <li>CCC/CQC and BIS safety certifications</li> </ul>	PMT-24V50W2BNJ		24 V	2.2 A	52.8 W	180-264 V <sub>AC</sub>	99 x 82 x 29	
	PMT-24V75W2BNJ			3.2 A	76.8 W		99 x 97 x 30	
	PMT-24V100W2BNJ			4.5 A	108 W		129 x 97 x 30	
	PMT-24V150W2BNJ			6.25 A	150 W		159 x 97 x 30	
	PMT-24V200W2BNJ			8.8 A	211.2 W		159 x 97 x 30	
	PMT-24V350W2BNJ			14.6 A	350.4 W		215 x 115 x 30	
	PMT-48V50W2BNJ		48 V	1.1 A	52.8 W	180-264 V <sub>AC</sub>	99 x 82 x 29	
	PMT-48V75W2BNJ			1.6 A	76.8 W		99 x 97 x 30	
	PMT-48V100W2BNJ			2.3 A	110 W		129 x 97 x 30	
	PMT-48V150W2BNJ			3.3 A	158.4 W		159 x 97 x 30	
	PMT-48V200W2BNJ			4.4 A	211.2 W		159 x 97 x 30	
	PMT-48V350W2BNJ			7.3 A	350.4 W		215 x 115 x 30	
<b>PMT2</b>  <ul style="list-style-type: none"> <li>Low profile 30 mm height</li> <li>IEC 60335, IEC 61558 approvals</li> </ul>	PMT-12V35W2BA□		12 V	3.0 A	36 W	90-264 V <sub>AC</sub>	99 x 82 x 29	
	PMT-12V50W2BA□			4.2 A	50.4 W		99 x 82 x 29	
	PMT-12V75W2BA□			6.0 A	72 W		99 x 97 x 30	
	PMT-12V100W2BA□			8.5 A	102 W		129 x 97 x 30	
	PMT-12V150W2BA□			12.5 A	150 W	90-132 V <sub>AC</sub> , 180-264 V <sub>AC</sub> (Selectable by Switch)	159 x 97 x 30	
	PMT-12V150W2CA□			12.5 A	150 W	90-264 V <sub>AC</sub>	159 x 97 x 30	
	PMT-12V200W2BM□			17.0 A	204 W		159 x 97 x 30	
	PMT-12V200W2BR□			17.0 A	204 W	90-132 V <sub>AC</sub> , 180-264 V <sub>AC</sub> (Selectable by Switch)	159 x 97 x 30	
	PMT-12V350W2BM□			29.0 A	348 W		215 x 115 x 30	
	PMT-12V350W2BR□			29.0 A	348 W		215 x 115 x 30	
	PMT-15V35W2BA			15 V	2.4 A	36 W	90-264 V <sub>AC</sub>	99 x 82 x 29
	PMT-15V50W2BA				3.4 A	51 W		99 x 82 x 29
	PMT-15V75W2BA		5.0 A		75 W	99 x 97 x 30		
	PMT-15V100W2BA		7.0 A		105 W	129 x 97 x 30		
	PMT-15V150W2BA		10.0 A		150 W	90-132 V <sub>AC</sub> , 180-264 V <sub>AC</sub> (Selectable by Switch)	159 x 97 x 30	
	PMT-15V150W2CA		10.0 A		150 W	90-264 V <sub>AC</sub>	159 x 97 x 30	
	PMT-24V35W2BA□		24 V	1.5 A	36 W	90-264 V <sub>AC</sub>	99 x 82 x 29	
	PMT-24V50W2BA□			2.2 A	52.8 W		99 x 82 x 29	
	PMT-24V75W2BA□			3.2 A	76.8 W		99 x 97 x 30	
	PMT-24V100W2BA□			4.5 A	108 W		129 x 97 x 30	
	PMT-24V150W2BA□			6.25 A	150 W	90-132 V <sub>AC</sub> , 180-264 V <sub>AC</sub> (Selectable by Switch)	159 x 97 x 30	
	PMT-24V150W2CA□			6.25 A	150 W	90-264 V <sub>AC</sub>	159 x 97 x 30	
	PMT-24V200W2BM□			8.8 A	211.2 W		159 x 97 x 30	
	PMT-24V200W2BR□			8.8 A	211.2 W	90-132 V <sub>AC</sub> , 180-264 V <sub>AC</sub> (Selectable by Switch)	159 x 97 x 30	
	PMT-24V350W2BM□			14.6 A	350.4 W		215 x 115 x 30	
	PMT-24V350W2BR□			14.6 A	350.4 W		215 x 115 x 30	
	PMT-30V35W2BA			30 V	1.2 A	36 W	90-264 V <sub>AC</sub>	99 x 82 x 29
	PMT-30V50W2BA				1.7 A	51 W		99 x 82 x 29
	PMT-30V75W2BA		2.5 A		75 W	99 x 97 x 30		
	PMT-30V100W2BA		3.6 A		108 W	129 x 97 x 30		
	PMT-30V150W2BA		5.0 A		150 W	90-132 V <sub>AC</sub> , 180-264 V <sub>AC</sub> (Selectable by Switch)	159 x 97 x 30	
	PMT-30V150W2CA		5.0 A		150 W	90-264 V <sub>AC</sub>	159 x 97 x 30	
	PMT-36V35W2BA		36 V	1.0 A	36 W	90-264 V <sub>AC</sub>	99 x 82 x 29	
	PMT-36V50W2BA			1.45 A	52.2 W		99 x 82 x 29	
	PMT-36V75W2BA			2.1 A	75.6 W		99 x 97 x 30	
	PMT-36V100W2BA			3.0 A	108 W		129 x 97 x 30	
PMT-36V150W2BA		4.3 A		154.8 W	90-132 V <sub>AC</sub> , 180-264 V <sub>AC</sub> (Selectable by Switch)	159 x 97 x 30		
PMT-36V150W2CA		4.3 A		154.8 W	90-264 V <sub>AC</sub>	159 x 97 x 30		

1) For options, please refer to the technical datasheet


## ECONOMIC

Series	Model Name <sup>1)</sup>	PFC	Output Voltage			Input Voltage Range	Dimensions in mm (L x W x H)	
			Voltage	Current	Power			
<b>PMT2</b>  <ul style="list-style-type: none"> <li>• Low profile 30 mm height</li> <li>• IEC 60335, IEC 61558 approvals</li> </ul>	PMT-36V200W2BM	●	36 V	5.9 A	212.4 W	90-132V <sub>AC</sub> , 180-264V <sub>AC</sub> (Selectable by Switch)	159 x 97 x 30	
	PMT-36V200W2BR			5.9 A	212.4 W		159 x 97 x 30	
	PMT-36V350W2BM			9.7 A	349.2 W		215 x 115 x 30	
	PMT-36V350W2BR			9.7 A	349.2 W		215 x 115 x 30	
	PMT-48V35W2BA	●	48 V	0.8 A	38.4 W	90-264V <sub>AC</sub>	99 x 82 x 29	
	PMT-48V50W2BA			1.1 A	52.8 W		99 x 82 x 29	
	PMT-48V75W2BA			1.6 A	76.8 W		99 x 97 x 30	
	PMT-48V100W2BA			2.3 A	110.4 W	90-132V <sub>AC</sub> , 180-264V <sub>AC</sub> (Selectable by Switch)	129 x 97 x 30	
	PMT-48V150W2BA			3.3 A	158.4 W		159 x 97 x 30	
	PMT-48V150W2CA			3.3 A	158.4 W	90-264V <sub>AC</sub>	159 x 97 x 30	
	PMT-48V200W2BM			4.4 A	211.2 W	90-132V <sub>AC</sub> , 180-264V <sub>AC</sub> (Selectable by Switch)	159 x 97 x 30	
	PMT-48V200W2BR			4.4 A	211.2 W		159 x 97 x 30	
	PMT-48V350W2BM			7.3 A	350.4 W		215 x 115 x 30	
	PMT-48V350W2BR			7.3 A	350.4 W		215 x 115 x 30	
	PMT-D1V75W2□A			5 V/12 V	5.0 A/4.0 A	73 W	90-264V <sub>AC</sub>	129 x 97 x 30
	PMT-D2V75W2□A			5 V/24 V	5.0 A/2.1 A	75.4 W		129 x 97 x 30

## HIGH PERFORMANCE

Series	Model Name	PFC	Output Voltage			Input Voltage Range	Dimensions in mm (L x W x H)		
			Voltage	Current	Power				
<b>PMR</b>  <ul style="list-style-type: none"> <li>• Built-in PFC</li> <li>• IEC 60335, IEC 61558 approvals</li> <li>• Low profile 30 mm height</li> </ul>	PMR-12V150W1AT	●	12 V	12.5 A	150 W	90-264V <sub>AC</sub> (DC input range 127-375V <sub>DC</sub> )	129 x 97 x 30		
	PMR-12V240W1AT			20.0 A	240 W		159 x 97 x 30		
	PMR-12V320W1AT			26.7 A	320.4 W		215 x 115 x 30		
	PMR-12V600W1BT			50.0 A	600 W		225 x 124 x 41		
	PMR-12V1K0W1BT <sup>2)</sup>	60.0 A	720 W	225 x 124 x 41					
	PMR-24V150W1AT	●	24 V	6.5 A	156 W	90-264V <sub>AC</sub> (DC input range 127-375V <sub>DC</sub> )	129 x 97 x 30		
	PMR-24V240W1AT			10.0 A	240 W		159 x 97 x 30		
	PMR-24V320W1AT			13.4 A	321.6 W		215 x 115 x 30		
	PMR-24V600W1BT			25.0 A	600 W		225 x 124 x 41		
	PMR-24V1K0W1BT <sup>2)</sup>			42.0 A	1,008 W	225 x 124 x 41			
	<b>NEW</b> PMR-24V1K5W1BTB			62.5 A	1,500 W	90-264V <sub>AC</sub>	204 x 127 x 40.5		
	PMR-36V150W1AT			●	36 V	4.3 A	154.8 W	90-264V <sub>AC</sub> (DC input range 127-375V <sub>DC</sub> )	129 x 97 x 30
	PMR-36V240W1AT					6.7A	241.2 W		159 x 97 x 30
	PMR-36V320W1AT	8.9 A	320.4 W			215 x 115 x 30			
	PMR-36V600W1BT	16.6 A	597.6 W			225 x 124 x 41			
	PMR-36V1K0W1BT <sup>2)</sup>	28.0 A	1,008 W			225 x 124 x 41			
	PMR-48V150W1AT	●	48V	3.3 A	158.4 W	90-264V <sub>AC</sub> (DC input range 127-375V <sub>DC</sub> )	129 x 97 x 30		
	PMR-48V240W1AT			5.0 A	240 W		159 x 97 x 30		
	PMR-48V320W1AT			6.7 A	321.6 W		215 x 115 x 30		
	PMR-48V600W1BT			12.5 A	600 W	225 x 124 x 41			
PMR-48V1K0W1BT <sup>2)</sup>	21.0 A			1,008 W	225 x 124 x 41				
<b>NEW</b> PMR-48V1K5W1BTC	31.25 A			1,500 W	90-264V <sub>AC</sub>	204 x 127 x 40.5			

## SPECIAL DESIGNS


Series	Model Name	PFC	Output Voltage			Input Voltage Range	Dimensions in mm (L x W x H)
			Voltage	Current	Power		
<b>PMS</b>  <ul style="list-style-type: none"> <li>• Support PMBus</li> <li>• Peak power for motor drives</li> <li>• Supports parallel connection of up to 6 power supplies for enhanced power output</li> </ul>	<b>NEW</b> PMS-24V750W1BTD	●	24 V	31.25 A	750 W	85-264V <sub>AC</sub>	177.8 x 101.6 x 40
	<b>NEW</b> PMS-24V1K2W1BTD			50.0 A	1,200 W		204 x 127 x 40.5
	<b>NEW</b> PMS-24V2K5W1BTD			104.2 A	2,500 W		271 x 127 x 40.5
	<b>NEW</b> PMS-48V750W1BTD	●	48 V	15.63 A	750 W	85-264V <sub>AC</sub>	177.8 x 101.6 x 40
	<b>NEW</b> PMS-48V1K2W1BTD			25.0 A	1,200 W		204 x 127 x 40.5
	<b>NEW</b> PMS-48V2K5W1BTD			52.1 A	2,500 W		271 x 127 x 40.5

1) For options, please refer to the technical datasheet



2) Coming soon

## Open Frame Power Supplies

### ECONOMIC




Series	Model Name <sup>1)</sup>	PFC	Output				Input Voltage Range	Dimensions (mm) (L × W × H)		
			Voltage	Convection		Forced Air		Open Frame		
				Current	Power	Current		Power		
 <ul style="list-style-type: none"> <li>Small footprint</li> <li>Multiple connector source options</li> </ul>	PJT-12V40WBA□		12 V	3.33 A	40 W	-	-	90-264 V <sub>AC</sub>	76.2 × 50.8 × 22.9	
	PJT-12V65WBA□			5.0 A	60 W	-	-		101.6 × 50.8 × 30	
	PJT-12V100WBA□	●		8.33 A	100 W	-	-		127 × 76.2 × 31	
	PJT-12V100WBB□			6.67 A	80 W	8.33 A	100 W		101.6 × 50.8 × 31.8	
	PJT-15V40WBA□		15 V	2.67 A	40 W	-	-	90-264 V <sub>AC</sub>	76.2 × 50.8 × 22.9	
	PJT-15V65WBA□			4.2 A	63 W	-	-		101.6 × 50.8 × 30	
	PJT-15V100WBA□	●		6.67 A	100 W	-	-		127 × 76.2 × 31	
	PJT-15V100WBB□			5.33 A	80 W	6.67 A	100 W		101.6 × 50.8 × 31.8	
	PJT-18V40WBA□		18 V	2.22 A	40 W	-	-	90-264 V <sub>AC</sub>	76.2 × 50.8 × 22.9	
	PJT-18V65WBA□			3.61 A	65 W	-	-		101.6 × 50.8 × 30	
	PJT-18V100WBA□	●		5.55 A	100 W	-	-		127 × 76.2 × 31	
	PJT-18V100WBB□			4.44 A	80 W	5.55 A	100 W		101.6 × 50.8 × 31.8	
	PJT-24V40WBA□		24 V	1.66 A	40 W	-	-	90-264 V <sub>AC</sub>	76.2 × 50.8 × 22.9	
	PJT-24V65WBA□			2.71 A	65 W	-	-		101.6 × 50.8 × 30	
	PJT-24V100WBA□	●		4.17 A	100 W	-	-		127 × 76.2 × 31	
	PJT-24V100WBB□			3.33 A	80 W	4.17 A	100 W		101.6 × 50.8 × 31.8	

### HIGH PERFORMANCE


Series	Model Name <sup>1)</sup>	PFC	Output				Input Voltage Range	Dimensions (mm) (L × W × H)		
			Voltage	Convection		Forced Air		Open Frame	Enclosed	
				Current	Power	Current				Power
 <ul style="list-style-type: none"> <li>Versatile configurations</li> <li>Conformal coating</li> </ul>	PJ-5V15W□NA		5 V	3.0 A	15 W	-	-	85-264 V <sub>AC</sub>	87.5 × 50 × 22	107.5 × 60 × 32
	PJ-12V15W□NA		12 V	1.3 A	15.6 W	-	-	85-264 V <sub>AC</sub>	87.5 × 50 × 22	107.5 × 60 × 32
	PJ-12V30W□NA			2.5 A	30 W	-	-		105 × 50 × 25.6	125 × 60 × 36
	PJ-12V50W□NA	●		4.3 A	51.6 W	-	-		132 × 50 × 26.6	162 × 60 × 36
	PJ-12V100W□□A	●		8.5 A	102 W	-	-		155 × 62 × 33.5	185 × 72 × 45
	PJ-12V150W□□A	●		12.5 A	150 W	-	-		160 × 75 × 37	188 × 85 × 47
	PJ-24V30W□NA			24 V	1.25 A	31.2 W	-		-	85-264 V <sub>AC</sub>
	PJ-24V50W□NA	●	2.1 A		50.4 W	-	-	132 × 50 × 26.6	162 × 60 × 36	
	PJ-24V100W□□A	●	4.3 A		103.2 W	-	-	155 × 62 × 33.5	185 × 72 × 45	
	PJ-24V150W□□A	●	6.3 A		150 W	-	-	160 × 75 × 37	188 × 85 × 47	
PJ-48V50W□NA	●	48 V	1.1 A	52.8 W	-	-	85-264 V <sub>AC</sub>	132 × 50 × 26.6	162 × 60 × 36	
 <ul style="list-style-type: none"> <li>Built-in PFC</li> <li>Power Boost up to 10 s</li> <li>Conformal coating</li> </ul>	PJB-24V100W□□A	●	24 V	4.3 A	103.2 W	-	-	85-264 V <sub>AC</sub>	155 × 62 × 33.5	185 × 72 × 45
	PJB-24V150W□□A	●		6.3 A	151.2 W	-	-		160 × 75 × 37	188 × 85 × 47
	PJB-24V240W□□A	●		10.0 A	240 W	-	-		180 × 84 × 42	212 × 98 × 59
	PJB-24V300W□□A	●		12.5 A	300 W	-	-		222 × 95 × 53.6	252 × 108 × 66

1) For options, please refer to the technical datasheet


## DIN Rail Modules

Product Type	Series	Model Name <sup>1)</sup>	Output		Input Current	Input Voltage Range	Dimensions (mm) (H x W x D)	
			Voltage	Current				
<b>Redundancy Module</b> 	CliQ II	DRR-20A	22-60 V	20.0 A	(1+1 Redundancy) = Nominal 2 x 12.5 A (N+1 Redundancy) = Nominal 2 x 10 A	22-60 V <sub>DC</sub>	121 x 50 x 122.1	
		DRR-20N					121 x 50 x 122.1	
		DRR-40A	22-60 V	40.0 A			(1+1 Redundancy) = Nominal 2 x 25 A (N+1 Redundancy) = Nominal 2 x 20 A	121 x 50 x 122.1
		DRR-40N						121 x 50 x 122.1
<b>Buffer Module</b> 	CliQ II	DRB-24V020AB□	24 V	20.0 A	Charging Mode: < 0.6 A	22.8-28.8 V <sub>DC</sub>		121 x 70 x 120.1
		DRB-24V040ABN		40.0 A				Charging Mode: < 0.6 A
<b>DC-UPS Module</b> 	CliQ II	DRU-24V40ABN	24 V	40.0 A	Charging Mode: 2.0 A ± 1.0 A	24-28 V <sub>DC</sub>	121 x 50 x 117.3	
	CHROME	DRU-24V10ACZ	24 V	10.0 A	Charging Mode: 0.5 A ± 0.1 A	24-28 V <sub>DC</sub>	91 x 71 x 55.6	
	CliQ M	DRU-24V10AMN	24 V	10.0 A	0.5 A, 1 A, 1.5 A, 2 A (typ.) (constant current)	18-30 V <sub>DC</sub>	124 x 38 x 117	
		DRU-24V20AMN		20.0 A	0.75 A, 1.5 A, 2.25 A, 3 A (typ.) (constant current)	18-30 V <sub>DC</sub>	124 x 38 x 117	
		DRU-24V40AMN		40.0 A	1 A, 2 A, 3 A, 4 A (typ.) (constant current)	18-30 V <sub>DC</sub>	124 x 50 x 117	

1) For options, please refer to the technical datasheet

Product Type	Series	Model Name	Nominal Voltage	Charging Current	Discharging Current	Dimensions (mm) (H x W x D)
<b>Battery Module</b> 	CliQ M	DRN-24V7AAEN	24 V	2.1 A Max	40.0 A Max	211.5 x 148 x 109.2

## Adapter

Series	Model Name	CC Code	Output			Input Voltage Range	Dimensions (mm) (L x W x H)
			Voltage	Current	Power		
<b>ADT</b>  <ul style="list-style-type: none"> <li>Compact size</li> <li>DoE Level VI and CoC Tier 2</li> </ul>	ADT-060A12AA	B-A	12 V	5.0 A	60 W	85-264 V <sub>AC</sub>	108 x 46 x 29.5
	ADT-060A12AB	B-A		5.0 A	60 W		108 x 46 x 29.5
	ADT-150B12AA	J-A		12.5 A	150 W	90-264 V <sub>AC</sub>	155 x 76 x 30
	ADT-060A15AA	B-A	15 V	4.0 A	60 W	85-264 V <sub>AC</sub>	108 x 46 x 29.5
	ADT-060A15AB	B-A		4.0 A	60 W		108 x 46 x 29.5
	ADT-060A19AA	B-A	19 V	3.2 A	60.8 W	85-264 V <sub>AC</sub>	108 x 46 x 29.5
	ADT-060A19AB	B-A		3.2 A	60.8 W		108 x 46 x 29.5
	ADT-120A19AA	M-A		6.15 A	120 W	90-264 V <sub>AC</sub>	138 x 68.5 x 24.5
	ADT-150A19AA	G-A	7.7 A	150 W	90-264 V <sub>AC</sub>	160 x 76.2 x 25.8	
	ADT-060A24AA	B-A	24 V	2.5 A	60 W	85-264 V <sub>AC</sub>	108 x 46 x 29.5
	ADT-060A24AB	B-A		2.5 A	60 W		108 x 46 x 29.5
	ADT-090A24AA	F-A		3.75 A	90 W	90-264 V <sub>AC</sub>	126 x 51 x 30
	ADT-120A24AA	F-A		5.0 A	120 W		138 x 68.5 x 24.5
	ADT-150A24AA	H-A		6.25 A	150 W		160 x 76.2 x 25.8
ADT-150C24AC	K-A	6.25 A		150 W	165.1 x 76.1 x 31.5		

# Global Operation & Service

## Asia

### Delta Electronics, Inc.

3 Tungyuan Road, Chungli Industrial Zone,  
Taoyuan County 32063, Taiwan, R.O.C.

TEL: +886 3 452 6107  
FAX: +886 3 452 7314

### Delta Electronics (Shanghai) Co., Ltd China Headquarters

No. 182 Minyu Road, Pudong,  
Shanghai, P.R.C. 201209

TEL: +86 21 6872 3988  
FAX: +86 21 6872 3996

### Delta Electronics (Thailand) PCL.

909 Soi 9, Moo 4, Bangpoo Industrial Estate  
(E.P.Z.), Pattana 1 Rd., T. Phrakasa, A. Muang,  
Samutprakarn 10280, Thailand

TEL: +66 2 709 2800  
FAX: +66 2 709 2827

### Delta Electronics India Pvt. Ltd.

Plot No. 43, Sector - 35, HSIIDC,  
Gurgaon, Haryana 122001

TEL: +91 124 4874 900  
+91 124 4169 040  
FAX: +91 124 4874 945

### Delta Electronics (Japan), Inc.

2-1-14 Minato-ku Shibadaimon,  
Tokyo, 105-0012, Japan

TEL: +81 3 5733 1111  
FAX: +81 3 5733 1211

### Delta Electronics (Korea), Inc.

1504, Byucksan Digital Valley 6-Cha,  
Gasan-dong, Geumcheon-gu, Seoul,  
153-704, Korea

TEL: +82 2 515 5303  
+82 2 515 5305  
FAX: +82 2 515 5302

### Delta Electronics (Australia) Pty Ltd

20-21, 45 Normanby Rd.  
Nothing Hill, VIC 3168, Australia

TEL: +61 9543 3720  
FAX: +61 9544 0606

### Delta Energy Systems (Singapore) Pte Ltd

4 Kaki Bukit Avenue 1  
#05-04, Singapore 417939

TEL: +65 6747 5155  
FAX: +65 6744 9228

## North America

### Delta Electronics (Americas) Ltd. North American Headquarters

46101 Fremont Blvd.  
Fremont, CA 94538, U.S.A.

TEL: +1 510 668 5100  
FAX: +1 510 668 0680

## Central & South America

### Delta Electronics International Mexico S.A. de C.V.

Centrum Park, Av. Gustavo Baz Prada 309  
Edificio E Planta Baja, Col. La Loma, C.P.

54030 Tlalnepantla, Estado de México  
TEL: +52 55 3603 9200

### Delta Electronics (Brasil) Ltda

Estrada Velha Rio São Paulo, 5300-  
Eugênio de Melo, 12247-001-São José dos  
Campos-SP- Brasil

TEL: +55 12 3932 2300

## Europe

### Delta Electronics (Netherlands) B.V. EMEA Headquarters

Zandsteen 15  
2132 MZ Hoofddorp, The Netherlands

TEL: +31 20 800 3900

Automotive Campus 260  
5708 JZ Helmond, The Netherlands

TEL: +31 40 800 3900

### Delta Greentech Elektronik (Turkey)

Şerifali Mah. Hendem Cad. Kule Sok. No: 16-A,  
Ümraniye, İstanbul, Turkey

TEL: +90 216 499 99 10  
FAX: +90 216 499 80 70



[www.DeltaPSU.com](http://www.DeltaPSU.com)

March 2025 (Rev. 01) - All information and specifications are subjected to change without prior notice.