# **Delta LED Driver LNA Arena Sport Series**

Dual DALI-2 & D4i and RDM/DMX Controls for Outdoor Lighting



#### **LED Drivers**

# Delta's New LNA Arena Sport Series LED Driver Illuminates Global Stadiums

Delta launches the advanced LED driver solution LNA Arena Sport Series for worldwide outdoor stadiums and high mast lighting. The Series is the extended version of the EUCO Arena Sport Series, which is specifically designed for the European market and gained huge success there. The LNA Series features 1,200 W, 1,600 W and 1,800 W outputs. It conforms to both DALI-2 & D4i and RDM/DMX protocols, suitable for smart lighting solutions.

This LNA Arena Sport Series offers unparalleled flexibility with programmable output current and dimming function (0.1%~100%). Besides, its constant Lumen Output (CLO) and Smart Timer Dim (STD) adjust lighting under various circumstances, improving energy saving while ensuring

consistent brightness. The Series features flicker-free and up to 33 fps strobe effects for HDTV broadcasting, providing immersive experiences for TV watchers. Additionally, it has an afterglow-free feature and high-accuracy, integrated power metering, allowing sophisticated lighting management and monitoring.

The Series features a wide input voltage range of  $187-528~V_{AC}$  for versatility and has robust surge protection to ensure reliable operation under demanding outdoor lighting environments. It also meets international safety certifications including EN 61347/UL8750/GB19510~(CCC)/RCM and BIS 15885, allowing it to operate in many countries.





#### **Product Information**

**LED Driver** > LNA ARENA SPORT Series (Global Version)

### 1,200 W



**LNA-1K2B20ABFGB** 187-528 V<sub>AC</sub> / 150-550 V<sub>DC</sub> / 1,200 W

https://www.deltapsu.com/en/products/led-driver/LNA-1K2B20ABFGB

#### 1,650 W



**LNA-1K6C20ABFGB** 187-528 V<sub>AC</sub> / 150-550 V<sub>DC</sub> / 1,650 W

https://www.deltapsu.com/en/products/led-driver/LNA-1K6C20ABFGB

# 1,800 W



**LNA-1K8C20ABFGB** 187-528 V<sub>AC</sub> / 150-550 V<sub>DC</sub> / 1,800 W

 $\underline{https://www.deltapsu.com/en/products/led-driver/LNA-1K8C20ABFGB}$ 

• Please contact your <u>local sales representative</u> for product availability. Alternatively, you may <u>leave us a message</u> and our sales representative shall get back to you.



#### **Product Information**

#### LED Driver > EUCO ARENA SPORT Series (EMEA Version)

#### 1,200 W



**EUCO-1K2200GCA** 187-528 V<sub>AC</sub> / 150-550 V<sub>DC</sub> / 1,200 W

https://www.deltapsu.com/en/products/led-driver/EUCO-1K2200GCA

#### 1,650 W



**EUCO-1K6200GCA** 187-528 V<sub>AC</sub> / 1

 $187-528 \ V_{AC} \ / \ 150-550 \ V_{DC} \ / \ 1,650 \ W$ 

 $\underline{https://www.deltapsu.com/en/products/led-driver/EUCO-1K6200GCA}$ 

# 1,800 W



**EUCO-1K8200GCA** 187-528 V<sub>AC</sub> / 150-550 V<sub>DC</sub> / 1,800 W

https://www.deltapsu.com/en/products/led-driver/EUCO-1K8200GCA

• Please contact your <u>local sales representative</u> for product availability. Alternatively, you may <u>leave us a message</u> and our sales representative shall get back to you.



#### **Features**

- Configurable channel address mode (1\*DT6 / 1\*DMX or 2/3\*DT6 / 2/3\*DMX)
- 187-528 V<sub>AC</sub> input voltage range
- Up to 97.5% high efficiency
- 700-2,000 mA programmable output current range
- 150-550 V<sub>DC</sub> output voltage range
- Built-in DALI-2 & D4i and RDM/DMX communication protocols
- 0.1-100% wide dimming range
- Low current ripple (typ.1%) for HDTV broadcasting
- Up to 33 fps strobe effects
- Afterglow-free feature
- High-accuracy integrated power metering
- Input surge protection: DM 10kV / CM 10kV

# **Applications**



Sports Stadium



Sports Arena



idustrial Lighting



High Mast Lighting